

# HP 3D Printing polymer materials portfolio selection guide<sup>1</sup>



	HP 3D HR PA 12 W	HP 3D HR PA 11	HP 3D HR PA 12, enabled by Evonik	HP 3D HR PA 12 GB	HP 3D HR PP enabled by BASF <sup>4</sup>
Rigid polymer					
Stiffness	●	●	●	★	■
Impact resistance	■	●	■	▲	■
Elongation	■	●	■	▲	■
Dimensional capability	★	●	★	●	■
Level of detail	★	★	●	●	■
Flat part	●	■	●	★	▲
Temperature resistance	■	▲	■	●	■
Chemical resistance <sup>2,3</sup>	●	●	●	n/a	★
Low moisture absorption	▲	▲	▲	▲	★
Lightweight	●	●	●	■	★

	HP 3D HR TPA, enabled by Evonik	BASF Ultrasint <sup>®</sup> TPU01	ESTANE <sup>®</sup> 3D TPU M95A	ESTANE <sup>®</sup> 3D TPU M88A
Elastomeric polymer				
Rebound (%)	★	●	●	●
Elongation at break (%)	●	●	★	●
Tensile strength (MPa)	●	●	★	●
Abrasion resistance (mm)	●	★	●	●
Biocompatibility	▲	★	★	★

★ Best   ● Good   ■ Fair   ▲ Not recommended

1. Based on internal HP testing, October 2022. For testing methodology and results, see [hp.com/go/3Dprintingmaterialswhitepapers](https://hp.com/go/3Dprintingmaterialswhitepapers). Please consult your local sales representative for more information.
2. For HP 3D High Reusability PA 11, PA 12, and CB PA 12, based on internal HP testing, June 2017. Tested with diluted alkalies, concentrated alkalies, chlorine salts, alcohol, ester, ethers, ketones, aliphatic hydrocarbons, unleaded petrol, motor oil, aromatic hydrocarbons, toluene, and DOT 3 brake fluid. For HP 3D High Reusability PP enabled by BASF, based on internal HP testing, May 2020, with tests for mechanical property retention, dimensional stability, and weight change after 7- and 30-day immersion with acids, bases, organic solvents, and aqueous solutions. Due to the material characteristics, extra tuning is required in part design and printing, compared to other rigid HP 3D Printing materials. For BASF Ultrasint<sup>®</sup> TPU01, based on testing by BASF, April 2020, according to ASTM D471 for select IRM oils and Fuel A.
3. For HP 3D High Reusability PP enabled by BASF, based on internal HP testing, May 2020, with tests for mechanical property retention, dimensional stability, and weight change after 7- and 30-day immersion with acids, bases, organic solvents, and aqueous solutions. Due to the material characteristics, extra tuning is required in part design and printing, compared to other rigid HP 3D Printing materials.